

**County of Mendocino  
FLEET OPERATIONS DIVISION  
SPECIFICATION, MOTOR VEHICLE**

**2016 OR NEWER MODEL YEAR 14,000# GVWR, CAB & CHASSIS  
REGULAR CAB, 4WD, DRW  
WITH FLATBED STAKESIDE DUMP BED WITH ELECTRIC OVER HYDRUALIC HOIST**

SPECIFICATION DATA:	MINIMUM REQUIREMENTS:	Meets Requirements	
		Yes	No
Body Style:	2 Door Cab and Chassis, DRW		
Cab to Axle Distance:	84.0 Inches		
Wheel Base:	169.0 Inches		
G.V.W.R:	14,000 Pounds.		
Conventional Towing Capacity:	16,000 Pounds		
Engine Type:	Gasoline. V-8		
Engine Size:	6.2 Liter 380 HP @ rated RPM		
Transmission:	6 Speed Automatic with Overdrive		
Transmission Shift Lever:	Factory Column Mounted		
Differential:	4.30:1 Rear Ratio, Limited Slip		
Suspension:	Heaviest Duty Available.		
Brakes:	Power ABS		
Steering:	Power		
Wheels:	(7 ea.) Mfr. Std Steel 17", 8 Lug		
Tires:	(7 ea.) LT245/75R17E All Season BSW		
Undercarriage Spare Tire Mount:	Yes		
Spare Tire:	Full Size		
Tire Air Pressure Monitoring System:	Yes, Factory		
Alternator / Battery:	200 Amp / Dual (2) 650 CCA		
Cooling System:	Heaviest Duty Available		
Fuel Capacity:	40 Gallons		
Seating Capacity:	3 Persons		
Seats, Front:	40/20/40 Split Bench		
Radio:	AM/FM Stereo, Factory		
Instrumentation:	Gauges		
Tilt Wheel/ Speed Control:	Yes, Factory		
Deep Tint Glass:	Yes, Factory		
Air Conditioning:	Yes, Factory		
Power Windows:	Yes, Factory		
Power Door Locks:	Yes, Factory		
Intermittent Windshield Wipers:	Yes, Factory		
Power Mirrors, Manual Telescoping Trailer			
Tow Mirrors with Power Heated Glass:	Yes, Factory		
Seat Covers:	Vinyl		
Floor Covering:	Vinyl or Rubber		
Floor Mats:	Heavy Duty Rubber		
Trailer Tow Package:	Yes, Factory		
Electric Brake Controller:	Yes, Factory		
Trailer Socket Adapter:	A RV 7 Blade to 6 Pole Round (center pin electric brake). Includes dust cover.		
Front License Plate Bracket:	Yes. Factory		
E85 Ethanol Compatible:			
Exterior/Interior Colors:	White / Black or Gray		

SPECIFICATION DATA:	MINIMUM REQUIREMENTS:	Meets Requirements	
		Yes	No
<b>Three (3) Matching Sets of Programmed Keys. All Keys Shall Function Identically, Including Remote Control Key Fobs:</b>	Yes. Factory		

**Dump Bed Body Specifications:**

Bed to be 96" x 144" built on 5" x 144" long sills with 11ga. 50,000psi high yield steel cross sills with maximum 18" spacing between cross sills. Cross sills to be 5.44" height.		
Floor to be 3/16" 36,000psi mild steel tread plate.		
Front, rear and side rails to have 2" x 4" reinforced stake pockets.		
Solid headboard bulkhead. Bulkhead to be 11ga high strength steel with intermediate post to tie into the long sills and corner post to be one piece box section secured to platform. Must have knee gussets welded to underside of platform side rails.		
Pull Tarp: PULLTARPS Super Shield Truck Tarp System. Manual unit designed for dump bed body and mounted on back of solid headboard bulkhead at height equal to the top of installed side panels Tarp Design: 18 ounce vinyl with side flaps. Tarp Color: Black.		
Side panels shall consist of 3 (three) each side 48"L x 40"H interlocking 3/4" plywood stake side panels set in stake pockets and marked for designation.		
Rear panels consist of 2 (two) 48"L x 40"H interlocking 3/4" plywood stake side panels set in stake pockets and marked for designation.		
Hoist to have a electric over hydraulic self contained hydraulic pump with lifting capacity at 45 degree angle with 4" x 12" double acting single lift cylinder. Hinges built into rear of subframe.		

SPECIFICATION DATA:	MINIMUM REQUIREMENTS:	Meets Requirements	
		Yes	No
Rear of truck frame to be furnished with a class V 2" receiver hitch with a RV 7 Blade (center pin electric brake) 6 way trailer plug wired into factory wiring harness. License plate mounting with license plate light. Dual hook eyes for safety chain hooks to be installed. Install a backup alarm and lights. Install 4 (four) rope hooks on each side and rear. Install rear mud flaps.			
Ladders located at both rear corners of body.			
Tool Boxes: Frame mounted underbody on both sides			
Tool Boxes: Frame mounted underbody on both sides. 60.0" Long x 18.0" High x 18.0" Deep. Black powder coated finish.			
Shovel Holders: 2 (two) shovel holders brackets mounted on both sides of the front solid headboard bulkhead.			
<b>REAR GATES.</b> Rear corners of the bed to have corner bolsters with two barn door style hinged gates. The gates will swing out and rest against the sides with a back latch for latching the gates back against the side panels while dumping. The gate shall be framed with 1 1/2" x 2" x .120 tubing. The corner bolsters shall be of 2"x2" x 3/16" heavy wall tubing. The gates and the corner bolsters shall be the same height as the side panels. The gates will have 3/4' plywood panels the same as the side panels. The gates will latch closed together in the middle where they meet.			
All lights to be D.O.T. approved. Lights in the body to be sealed flush rubber mounted. Install rear Identification light cluster. All lights to be LED.			
Body, subframe and all body installed parts to be painted black in color			
Body to have all D.O.T. reflective tape on all sides.			

SPECIFICATION DATA:	MINIMUM REQUIREMENTS:	Meets Requirements	
		Yes	No

**For the purpose of "Fleet" standardization, only the following name plates will be accepted as qualifying bids.**

Representative Vehicles: Ford F350SD, Chevrolet Silverado 3500HD,  
 GMC Sierra 3500HD, Ram 3500  
 Base model - No options

**Please list Vehicle you are submitting Bid on:**

Year \_\_\_\_\_ Make \_\_\_\_\_ Model \_\_\_\_\_

Lead Time \_\_\_\_\_

**NOTE:** If "YES" is checked that means "as specified". If "NO" is checked that means the specification is different. If "NO" is checked, then a separate sheet of paper must accompany your bid package explaining the exception to the specification.

**FOB** Destination W-Full Fuel Tank

**Documentation prepared as follows.**

County of Mendocino  
 841 Low Gap Road  
 Ukiah Ca 95482

A signature is required on every specification sheet:

Company Name: \_\_\_\_\_

Signature: \_\_\_\_\_

Print Name: \_\_\_\_\_

**NOTICE:** YOUR BID WILL BE REJECTED IF YOU FAIL TO COMPLETE AND RETURN THE SPECIFICATION SHEET, 4 PAGES, ALONG WITH THE "INVITATION FOR BID" FORM COMPLETED AND SIGNED.